



69.95 EUR incl. 19% VAT, plus <u>shipping</u>

- 100/240V
- 192W !
- Model: STD-12160
- FANLESS !

Support: 4pol Mini DIN Connector Pinout

For connecting PicoPSU-150-XT/PicoPSU-160-XT to the standard 230V house power net. 192W max.

- Dimensions: 183 x 81 x 42 mm
- Connector : 4 pin Mini DIN
- Efficiency : >=87%
- CEC, Energy Star Level V & ErP Stage 2 & NRCan
- No Load Power Consumption Less Than 0.5W

PicoPSU-adapter cable 4 pin Mini DIN to Mini-Fit-JR included. Power cord (cold devices connector) not included.

Model	Output Voltage	Output Current	Watt	
STD-12160	12.0V	16.0A	192W	
Input				
Voltage	100-240 VAC			
Line Frequency	50-60Hz			
Current	2.8A Max.			
Protection	Internal Primary Current Fuse	e		
Configuration	IEC60320 / C14			
Output				
Load Regulation	± 5% (Typical)			



Pipplo	2. 5% V/n n Max, for Output Voltage @ Full Load		
Ripple Transient Response	3~5% Vp-p Max. for Output Voltage @ Full Load 0.5mS for 50% Load Change Typical		
Holdup Time	10mS @ Full Load		
Holdup Time	Short Circuit Protection/ Over Voltage Protection/ Over Current		
Protection			
	Protection/Over Temperature Protection		
DC Cord	UL2464 / 16AWG		
Ferrite Core	No (Optional)		
	Safety Approvals		
	CB / UL / cUL / FCC / GS / CE / PSE / BSMI / CCC / RCM		
	Electrical		
Topology	LLC		
Dielectric Withstand	3,000 VAC Primary – Secondary		
Leakage Current	3.5mA @ 3 Pin		
Efficiency	Engergy Star Level V, ErP Stage 2 & NRCan Certified		
EMI Conduction&Radiation	Compliance to EN55022 Class B		
Harmonic Current	Compliance to EN61000-3-2,3		
EMS Immunity	Compliance to EN61000-4-2,3,4,5,6,8,11		
MTBF	300,000 Calculated Hours at 25°C, by Telcordia SR-332		
	Environmental		
Operaturing Temperature	0 to +40°C		
Storage Temperature	-20 to +80°C		
Relative Humidity	Operating: 20 to 80% RH		
	Storage: 10 to 90% RH		
Cooling	Natural Convection Cooling		
	Mechanical		
Case Dimension	L183 x W81 x H42 (mm)		
Weight	850g (Ref.)		