

2059.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Kabylake-U Series SoC Processor
- Support ITPS power supply (9~36V DC-in)
- 8 * PoE ports

MB Model	<ul style="list-style-type: none"> - JNF752-7100U (Core i3) / (TDP 15W) - JNF752-7200U / 7300U (Core i5) / (TDP 15W) - JNF752-7600U (Core i7) / (TDP 15W) <p>The model will be ordered according to the CPU purchase status, and the detailed situation is recommended to contact the sales.</p>
Part No	<ul style="list-style-type: none"> - HBF752-7100-B (non-WIFI)/HBF752W-7100-B (WIFI) - HBF752-7200-B (non-WIFI)/HBF752W-7200-B (WIFI) - HBF752-7300-B (non-WIFI)/HBF752W-7300-B (WIFI) - HBF752-7600-B (non-WIFI)/HBF752W-7600-B (WIFI) <p>The model will be ordered according to the CPU purchase status, and the detailed situation is recommended to contact the sales.</p>
BIOS	- AMI Flash ROM
CPU/Chipset	- Intel® Kabylake-U Core-i SoC Processor
Memory	- Support 2 * DDR4 2133MHz SO-DIMM slots up to 32GB
Storage	<ul style="list-style-type: none"> - Support 2 * 2.5" SATA Device tray (Removable hard drive) - Support 1 * Mini-PCIe slot (full size, only for mSATA)
Network	- 1 * Intel® i219LM & 1 * Intel® i210AT GbE
Expansion	<ul style="list-style-type: none"> - 2 * Mini PCIe (full-size, for WiFi/3G/4G/ Capture Card module expansion) - 1 * Mini-PCIe slot (USB only, full size, for 4G LTE + GPS expansion)

Rear Panel I/O	<ul style="list-style-type: none"> - 4 * USB 2.0, 4 * USB 3.0 - 1 * HDMI (Max. resolution:4096 x 2304@24Hz) - 1 * VGA (Max. resolution:1920 x 1080@60Hz) - 2 * RJ45, 8 * 1000M PoE (23W/per port) - 1 * Line-out, 1 * MIC - 2 * COM (RS232/RS422/RS485) - 1 * DC 9~36V_3PIN Industrial connector, 1 * DC 48~52V_2PIN Industrial connector - 1 * Clear COMS Button - 1 * AT Mode setting_2PIN Industrial connector - 2 * Antenna holes (Optional)
Front Panel I/O	<ul style="list-style-type: none"> - 1 * Power Button + LED, 1 * Reset Button, 1 * HDD LED - 1 * Power on-off_2PIN Industrial connector - 2 * COM (RS232) - 2 * GPIO (1*DI & 1*DO/ 6 BIT) (Support Isolated) - 1 * LVDS out (Max. resolution:1920 x 1080@60Hz) - 3 * SIM card holes - 2 * 2.5" SATA Device tray (Easy to change HDD) - 1 * GND Hold - 1 * CAN Bus (DB9 Type_Optional) - 3 * Antenna holes (Optional)
Power Source	<ul style="list-style-type: none"> - DC 9~36V INPUT for SYSTEM (Support Boot & Shutdown delay function_ITPS) - DC 48~52V INPUT for POE LAN
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS
Temperature	<ul style="list-style-type: none"> - Operating Temperature: -20 ~ 70° C - Storage Temperature: -20 ~ 70° C
Dimensions	<ul style="list-style-type: none"> - 232 (W) x 231.4 (D) x 103 (H) mm
Packing	<ul style="list-style-type: none"> - Net Weight: 2.7KG - Gross Weight: 3.7KG
OS Support	<ul style="list-style-type: none"> - Windows 10, Linux
Warranty	<ul style="list-style-type: none"> - 2 Years limited warranty