


309.00 EUR
incl. 19% VAT, plus shipping

- LGA1200 Socket !
- H410 Chipset !
- ATX !

- Intel® LGA1200 Socket supports 10th Gen. Core Processor (Max. 100W)
- Intel® Comet Lake-S H410 Chip
- 2* DDR4 2933/2666MHz up to 64GB
- Realtek HD Audio
- 1* Intel® i225-LM 2.5GbE, 1* Intel® i219-LM GbE
- 4* SATA III (6Gb/s), 1* M.2 (M key) , 1* PCI-E x16, 1* PCI-Ex4, 5* PCI slots
- 2* RS232/422/485 (COM1/2), 4* RS232, 4* USB3.2, 5* USB2.0
- Support VGA / HDMI Output
- ATX Power Input
- ATX Form Factor (305 * 220 mm)

| | |
|---|---|
| Model | – JLA0H-00<br>– JLA0H-02: Support TPM2.0 |
| Form Factor | – ATX (305 * 220mm) |
| Processor System | – Intel® LGA1200 Socket supports 10th Gen. Core Processor (Max. 100W)<br>– Intel® H410 Express chipset<br>– AMI 256Mb Flash ROM BIOS |

| | |
|---|---|
| Expansion Slot | – 1* M.2 (M-key, 2242/2280, SATA Interface, CO-lay SATA4)<br>– 4* SATA4 (Co-lay M.2)<br>– 1* PCIe x16 + 1* PCIe x4 slot<br>– 5* PCI slots |
| Memory | – 2* LONG DIMM DDR4 2933/2666 MHz DRAM up to 64GB |
| Graphics | – Intel® HD Graphics, shared memory<br>– 1* VGA (Max Resolution: 1920×1080@60Hz)<br>– 1* HDMI 1.4 (Max Resolution: 4096×2160@30Hz)<br>– Support Dual Displays |
| Ethernet | – 1* Intel® i225-LM 2.5GbE<br>– 1* Intel® i219-LM GbE |
| Audio | – HD audio: Realtek ALC662 or ALC888<br>– Line-Out, Line-in, MIC |
| SATA | – 4* SATAIII (6.0Gb/s) |
| Rear I/O | – 1* VGA<br>– 1* HDMI<br>– 2* RJ45<br>– 4* USB3.2 (Gen. 1)<br>– 2* USB2.0<br>– Line-in, Line-out, MIC<br>– 2* RS232/422/485 (support 5/12V TTL)<br>– 1* PS/2 |
| Internal I/O | – 2* USB 2.0<br>– 1* USB2.0 (Erect)<br>– 4* RS232 (COM3/4 support 5/12V TTL)<br>– 4* SATAIII (6.0Gb/s , SATA4 Co-lay M.2 M key)<br>– 1* Parallel (Co-lay GPIO)<br>– 1* GPIO (16 bit, Co-lay Parallel)<br>– 1* Chassis intrusion<br>– 1* Audio Header<br>– 1* SMBUS / I2C<br>– 1* AT mode<br>– 1* TPM2.0 (option) |
| Watchdog Timer | – From Super I/O to drag RESETCON#<br>– 256 segments (10sec ~ 255min) |
| Power | ATX PWR, AT/ATX Supported<br>– AT: Directly PWR on as Power input ready<br>– ATX: Press Button to PWR on after Power input ready |
| Compliance | – CE, FCC, RoHS, REACH |
| Temperature | – Operating: 0°C ~ 60°C<br>– Storage: -20°C ~ 85°C<br>– Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| OS Support | – Windows 10, Linux |